

Port of Sundsvall – Tugboats

The port owns two conventional tugboats, primarily used for assistance and icebreaking but also for other assignments.

For further information and ordering of tugboat services, please contact:

e-mail: tugassistance@sundsvallshamn.se

Tugboat Captain

Mats Lundberg

+4670-3193540

mats.lundberg@sundsvallshamn.se

Tugboat regulations

For the Port of Tunadal and Sundsvall Oil Port

The following minimum requirements apply, whenever a tank vessel arrives to or departs from the port:

Vessel = 8 000 DW with no additional maneuver equipment – assistance by one tugboat.

Vessel = 14 000 DW with functioning additional maneuver equipment – one tugboat (safety boat).

§5 in Port administration for Sundsvalls Municipality applies to all vessel traffic to and from the Port areas.

Special requirements for large tank vessels

Any tank vessel equal to or larger than any of these measures is considered to be large:

Dwt 30 000, Length 200m, Width 30m, Draft 10m.

Restrictions for tank vessels

Wind (average): Ballast 8 m/s, Cargo 10 m/s.

Visibility: Minimum 1Nm.

Vessel equal to or larger than Dwt 50000 should be assisted by 2 pilots. Maneuvering at quay shall be done in daylight.

Tugboat requirements, at maximum number of 4

Minimum engine power for tugboats: Dwt of the vessel/10 minus any Hp on thruster.

Minimum Bollard pull for tugboat/s: Dwt of the vessel/10 minus any Hp on thruster/100 = Bollard pull (in tons).